

01-15-04

2815

#16

PTO/SB/21 (08-03)

Approved for use through 07/31/2006. OMB 0651-0031  
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.


<b>TRANSMITTAL FORM</b> (to be used for all correspondence after initial filing)	Application Number	09/871383	
	Filing Date	05.31.2001	
	First Named Inventor	Edlin Solomon	
	Art Unit	2815	
	Examiner Name	Joseph Nguyen	
Total Number of Pages in This Submission	19	Attorney Docket Number	—

ENCLOSURES (Check all that apply)		
<input type="checkbox"/> Fee Transmittal Form	<input checked="" type="checkbox"/> Drawing(s)	<input type="checkbox"/> After Allowance communication to Group
<input type="checkbox"/> Fee Attached	<input type="checkbox"/> Licensing-related Papers	<input type="checkbox"/> Appeal Communication to Board of Appeals and Interferences
<input checked="" type="checkbox"/> Amendment/Reply	<input type="checkbox"/> Petition	<input type="checkbox"/> Appeal Communication to Group (Appeal Notice, Brief, Reply Brief)
<input type="checkbox"/> After Final	<input type="checkbox"/> Petition to Convert to a Provisional Application	<input type="checkbox"/> Proprietary Information
<input type="checkbox"/> Affidavits/declaration(s)	<input type="checkbox"/> Power of Attorney, Revocation	<input type="checkbox"/> Status Letter
<input type="checkbox"/> Extension of Time Request	<input type="checkbox"/> Change of Correspondence Address	<input type="checkbox"/> Other Enclosure(s) (please identify below):
<input type="checkbox"/> Express Abandonment Request	<input type="checkbox"/> Terminal Disclaimer	RECEIVED JAN 20 2004 TECHNOLOGY CENTER 2800
<input type="checkbox"/> Information Disclosure Statement	<input type="checkbox"/> Request for Refund	
<input type="checkbox"/> Certified Copy of Priority Document(s)	<input checked="" type="checkbox"/> CD, Number of CD(s) 1	
<input type="checkbox"/> Response to Missing Parts/Incomplete Application	Remarks	
<input type="checkbox"/> Response to Missing Parts under 37 CFR 1.52 or 1.53		
<b>SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT</b>		
Firm or Individual name	Edlin Solomon	
Signature		
Date	01.11.2004	

CERTIFICATE OF TRANSMISSION/MAILING		
I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below.		
Typed or printed name	Edlin Solomon	
Signature		Date 01.11.2004

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.



Examiner -- Joseph Nguyen  
Applicant -- Edlin Solomon  
Reply mailed 01.11.2004.  
Application 09/871383(20020089000-A1).  
Art unit 2815.Mailing date 9.27.2002.

Reply No.6 to Notice received on 10.18.2002.

H01L 29/06  
H01L 29/70

## BIDIRECTIONAL BIPOLAR STATIC INDUCTION DEVICE

"between paragraph 0005 and 0007". This result is achieved by an impurity concentration near the gate is high enough.

"paragraph 0010". Though the structure of the transistor is symmetric the operating duty of the channel that is near the drain of the transistor essentially differs from the operating duty of the channel that is near its source. The electrical field reduces the concentration of holes in the former and increases their concentration in the latter. Owing to this, the hole concentration along an axis perpendicular to surface is trapezoidal in zero approximation. It puts certain restrictions both on the design parameters of BSIT and on designing of circuits in which these transistors are applied. Introduced in the structure the thick channel provides increasing of operating current (without latch). A threshold voltage of the thick channel is lower than that of the ordinary channel. Algorithm of control of the offered transistor (offered) under typical circumstances is more complicated than that of the transistor described above ([1]) [3]. Let potentials of the gates are equal to potentials of the source and drain accordingly. The electrons flowing to the drain electrode can cause emission of the holes from the gate, disposed near the drain. The holes flow to the gate, disposed near the source. Part of the holes flow into the channel and causes the flow of the electrons to the drain. So, there is a positive feedback in the device. Device is latched. On-voltage of the latched device is more than on-voltage of the open transistor. To preserve the feedback it is necessary to provide so that electrons might flow to the drain free. It depends both on a control circuit and on the construction of the transistor. The part of the control circuit is represented on fig.10 of the application. Electrons can (might) flow to the drain through open transistor 113 or 123. (In the simplest variant the thick channel drain electrode has been connected to the ordinary channel drain electrode with a conductor.) The construction of the transistor provides the way for electrons to the drain through the thick channel while transistor is closed or is being switched off. The potential of the thick channel drain electrode has to be positive or zero or little negative relative to the potential of the drain electrode of ordinary channel. The high drain voltage extracts electrons from the thick channel which is disposed near the source. The potential of the thick channel source electrode has to be positive so that the thick channel is closed.(It is allowed that the potential of the thick channel source electrode might equal zero, if the threshold voltages equal approximately 0.2 volt).  
(To achieve optimum characteristics three rather than two different levels of voltages should be applied to the transistor gates. One of the voltages to the gate is about zero relatively to the nearby source, with the transistor channel closed, while the voltage applied to the gate near the drain should be about 0.4 V with the channel slightly open and the gate emit(ting) very low hole